

FISA TEHNICA

LEGEND

November 2017

Tipul produsului	EN 650	Covor PVC de uz rezidential	Covor PVC cu suport de pasla
Clasa de uzura	ISO 10874		
	Clasa	23	32

Descriere



	ISO 24346	3,5 mm		ISO 24341	25 m (15-25) 22 m (15-22)
				Lungime + Latime	2,5/3/3,5 m 4 m
	ISO 24340	0,5 mm		EN ISO 717/2	17 dB
				Izolare fonica la impact	
	ISO 23997	2,470 kg/m²		ISO 24343-1	<0,35mm
				Marcaj rezidual	

Caracteristici optionale

	ISO 23999	< 0,1 %		Rezistenta la foc	
	Stabilitate dimensionala		EN 13501-1	Bfl-s1	Bfl-s1
				No 327/BP/17	
	EN 12524	Potrivit pentru incalzirea in pardoseala. Temperatura suprafetei produsului nu trebuie sa depaseasca 27 °C.		Rezistenta la bacterii si ciuperci:	
	Rezistenta termica			Nu contribuie la raspandirea infectiilor	
	EN 13893	0,63			
	Slip resistance				

 Ramp test - DIN 51130 **R10**
 (WESTWOOD 1, WESTWOOD 2)

 Rezistenta Electrica: **EN 1081**: 9*109 Ω

 Comportament electricitate statica: **EN 1815**: 0,9 kV

 Fabricat in Serbia
 TARKETT

EN 14041 : 2004